
MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY / UNDERTAKING

- 1.1. PRODUCTS IDENTIFICATION: New Stronger-Faster Gorilla Glue**
- 1.2. USE OF SUBSTANCE:** Polyurethane adhesive for wood and wood substrates
- 1.3. COMPANY:** The Gorilla Glue Company
4550 Red Bank Expressway
Cincinnati
OH 45227
Telephone Number: (513) 271 3300
Fax Number: (513) 527 3742
- 1.4. EMERGENCY TELEPHONE:** (513) 271 3300

2. HAZARDS IDENTIFICATION

Harmful by inhalation. Irritating to eyes, respiratory system and skin. May cause sensitization by inhalation and skin contact.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical name	CAS No.	% content
Urethane prepolymer	trade secret	40-50
Polymeric MDI*	9016-87-9	50-60

*Polymeric MDI is a mixture of 4,4'-Diphenylmethane-diisocyanate, isomers and homologues.

4. FIRST-AID MEASURES**Inhalation:**

If aerosol or vapour is inhaled in high concentrations: Move affected individual to fresh air and keep him warm, let him rest. If there is difficulty in breathing; call a doctor.

Eye contact:

Flush eyes for at least 10 minutes while holding eyelids open. Contact a doctor.

Skin contact:

Remove contaminated clothes immediately, and wash skin with a cleanser based on polyethylene glycol or with plenty of warm water and soap. Consult a doctor in the event of a skin reaction.

Ingestion:

Product is not intended to be ingested or eaten. If this product is ingested, severe irritation of the gastrointestinal tract may occur, and should be treated symptomatically.

Do not induce the patient or animal to vomit. Call a doctor, ambulance or seek veterinarian assistance immediately.

MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

5. FIRE-FIGHTING MEASURES**Upper flammable limit (UFL):**

Not determined

Lower flammable limit (LFL):

Not determined

NFPA:

Health – 3, Flammability – 1, Reactivity – 1

HMIS:

Health – 3, Flammability – 1, Reactivity – 1

General fire hazards:

Down-wind personnel must be evacuated. Do not reseal contaminated containers; a chemical reaction generating carbon dioxide gas pressure may occur resulting in rupture of the container. Dense smoke is emitted when product is burned without sufficient oxygen. When using water spray, boil-over may occur when product temperature reaches the boiling point of water, and the reaction forming carbon dioxide will accelerate. MDI vapour and other gases may be generated by thermal decomposition.

Special hazards in fire:

In case of fire, formation of carbon monoxide, carbon dioxide, nitrogen oxide, isocyanate vapour, and traces of hydrogen cyanide is possible.

Extinguishing Media:

Carbon dioxide, dry powder, and foam. In cases of large scale fires, alcohol-resistant foams are preferred. If water is used, it should be used in very large quantities. The reaction between water and isocyanate may be vigorous.

Required special protective equipment for fire-fighters:

Fire fighters should wear full-face, self-contained breathing apparatus and impervious protective clothing. Fire fighters should avoid inhaling any combustion products.

6. ACCIDENTAL RELEASE MEASURES**Personal precautions:**

Wear full-protective clothing and respiratory protection as required maintaining exposures during clean-up below the applicable exposure limits.

Environmental precautions:

Do not discharge spillage into drains.

Clean-up procedures:

Remove mechanically; cover remainders with wet absorbent material (e. g. sand, earth, sawdust). After approx. one hour transfer to waste container and do not seal (evolution of CO₂). Keep damp in a safe ventilated area for several days.

MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

7. HANDLING AND STORAGE**Handling:**

Avoid contact with skin and eye. Do not smoke, eat and drink at the work-place.

Ventilation: If vapour or mist is generated during processing or use, local exhaust ventilation should be provided to maintain exposures below the applicable limits.

Personal protection: see Section 8.

Storage

Keep product away from sources of alcohols, amines, or other materials that react with isocyanates. Avoid prolonged heating above 160°C/320°F. Store the product in tightly closed containers in a well-ventilated place and in accordance with national regulations. Keep out of reach of children.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

For exposure controls see Section 15.

Component exposure limits:

Name	CAS no.	Type	ppm	mg/m ³
4,4'-Diphenylmethane diisocyanate	101-68-8	OSHA PEL	0.02	0.2
		ACGIH (TLV-TWA)	0.005	

Personal protection equipment:**General:**

Wear suitable protective clothing, protective gloves and protective goggles/mask.

Suitable materials for safety gloves:

Natural rubber/natural latex – NR (≥ 0.5 mm)

Polychloroprene – CR (≥ 0.5 mm)

Nitrile rubber – NBR (≥ 0.35 mm)

Butyl rubber – IIR (≥ 0.5 mm)

Fluorinated rubber – FKM (≥ 0.4 mm)

Respiratory protection:

Required in insufficiently ventilated working areas and during spraying. An air-fed mask, or for short periods of work, a combination of charcoal filter and particulate filter is recommended.

Eyes protection:

Chemical goggles or full face shields are recommended. An eyewash fountain and safety shower should be available in the work area. Contact lenses should not be worn when working with this product.

Skin protection:

Wear special gloves and working clothes to avoid skin irritation or sensitization. Depending on operation, chemical resistant boots, overshoes, and apron may also be required. Suitable materials for clothing: Polyethylene/ethylene vinyl alcohol laminates (PE/VAL) has been reported as an effective material of construction for chemical protective clothing for MDI.

MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical form:	Liquid
Color:	Dark-Brown
Odour:	Earthy, musty
Boiling point:	>300°C
Flash point:	>250°C
Vapour pressure:	<0,00001 mbar at 20° C (diphenyl-methane-diisocyanate)
Specific gravity:	Approx. 1,14 g/cm ³ at 20° C
Viscosity:	4,000 – 7,000 mPa.s at 25°C (Brookfield sp. 6/20 rpm)
Solubility in water:	reacts
Percent VOC:	0%

10. STABILITY AND REACTIVITY**Stability:**

The product is stable under the recommended handling and storage conditions (see section 7).

Hazardous decomposition products:

By exposure to high temperature, hazardous decomposition products may develop, such as isocyanate vapour and mist, carbon dioxide, carbon monoxide, nitrogen oxide, and traces of hydrogen cyanide.

Hazardous reaction:

Exothermic reaction with amines and alcohols; reacts with water forming heat, CO₂, and insoluble polyurea. The combined effect of CO₂ and heat can produce enough pressure to rupture a closed container.

11. TOXICOLOGICAL INFORMATION**Acute Toxicity:**

LD50 oral, rat: > 5000 mg/kg

Skin and mucous membrane compatibility, rabbit: Skin 8 hour's exposure – slight reddening.

Eyes – moderate reddening and slight swelling.

Inhalation:

Over-exposure may cause irritating effects on nose throat and respiratory tract.

Skin contact:

Prolonged or repeated contact may result in tanning and irritating effects.

Eye contact:

Over-exposure may cause irritating effects on eyes.

MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

12. ECOLOGICAL INFORMATION

Do not allow the product to escape into waters, wastewater or soil.

Biodegradability:	0% after 28 days
Acute fish toxicity:	LC0 > 1,000 mg/l (96 hrs.)
Toxicity for daphnia:	EC 50 > 1,000 mg/l (24 hrs.)
Acute bacteria toxicity:	EC 50 > 100 mg/l (3 hrs.)

13. DISPOSAL CONSIDERATIONS

The product remnants are classified as chemical waste. Dispose of waste according to Local, State, Federal, and Provincial Environmental Regulations.

14. TRANSPORT INFORMATION

This preparation is not classified dangerous according to international transport regulations ADR/RID/IMDG/IATA.

Other information: This product is not dangerous cargo. Irritating to skin and mucous membranes. Keep separated from foodstuffs.

15. REGULATORY INFORMATION

This product and its components are listed on the TSCA 8(b) inventory.

Symbol:



Hazard designation:

Xn – Harmful.

Contains:

4,4'- Diphenylmethane diisocyanate (MDI), isomere.

R-phrases:

R20	Harmful by inhalation.
R36/37/38	Irritating to eyes, respiratory system and skin.
R42/43	May cause sensitization by inhalation and skin contact.

S-phrases:

S23	Do not breathe gas/fumes/vapour/spray.
S36/37	Wear suitable protective clothing and gloves.
S45	In case of accident or if you feel unwell, seek medical advice immediately. (show the label where possible).

Any existing national regulations on the handling of isocyanates must be observed.

MATERIAL SAFETY DATA SHEET

NEW STRONGER-FASTER GORILLA GLUERevision Date: 26/01/2007

16. OTHER INFORMATION

The information herein is presented in good faith and believed to be accurate as of the effective date given. However, no warranty, expressed or implied, is given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or Provincial, and Local laws.

The Gorilla Glue Company does not test on animals, nor do we require our suppliers to test on animals. Any information provided in this MSDS is based on existing scientific testing of the various raw materials, and is not commissioned by this Company.

'1. Technology Supplies Limited (Company registration number 2285483) Whose registered office is Phoenix House, Tern Hill, Market Drayton, Shropshire, TF9 3PX ('Technology Supplies) is providing this data sheet on an 'as is' basis and makes no representations or warranties of any kind with respect to this data sheet or its contents and disclaims all such representations and warranties. In addition, Technology Supplies makes no representations or warranties about the accuracy, completeness, or suitability for any purpose of the information published in this data sheet. The information contained within this data sheet may contain technical inaccuracies or typographic errors. All liability of Technology Supplies howsoever arising for any such inaccuracies or errors is expressly excluded to the fullest extent permitted by law.

2. Neither Technology Supplies nor any of its directors, employees or other representatives will be liable for loss or damage arising out of connection with reliance upon this data sheet. This is a comprehensive limitation of liability that applies to damages of any kind, including (without limitation) compensatory, direct, indirect or consequential damages, income or profit, loss of or damage to property and claims of third parties.

3. Notwithstanding the foregoing, none of the exclusions and limitations in clauses 1 and 2 are intended to limit any rights you may have as a consumer under local law or other statutory rights which may not be excluded in any way to exclude or limit Technology Supplies for any liability for death or personal injury resulting in our negligence.'