

**MATERIAL SAFETY DATA SHEET****LIQUID POLYSTYRENE CEMENT**

Revision Date: 18/04/2005

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND THE COMPANY / UNDERTAKING****1.1 PRODUCTS IDENTIFICATION:** Liquid Polystyrene Cement**1.2 USE OF SUBSTANCE:** No information supplied**1.3. COMPANY:** Jarvis Manufacturing Co Ltd  
JBB House  
6 Hammond Avenue  
Whitehill Industrial Estate  
Reddish  
Stockport  
SK4 1PQ  
**Telephone Number:** 0161 480 2002  
**Fax Number:** 0161 429 6213**1.4. EMERGENCY TELEPHONE:** 0161 480 2002**2. HAZARDS IDENTIFICATION**

Flammable. Repeated exposure may cause skin dryness or cracking. Vapours may cause drowsiness and dizziness.

CLASSIFICATION:  
R10, R66, R67

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

| Ingredient Name    | EC No     | CAS No   | Content | Risk        |
|--------------------|-----------|----------|---------|-------------|
| BUTYL ACETATE-norm | 204-658-1 | 123-86-4 | 60-100% | R10 R66 R67 |

The full text for all R-Phrases are shown in Section 16

**4. FIRST-AID MEASURES****General Information:**

Move the exposed person to fresh air at once. Get medical attention if any discomfort continues.

**Inhalation:**

Move the exposed person to fresh air at once. If breathing stops, provide artificial respiration. Keep the affected person warm and at rest. Get prompt medical attention.

---

**MATERIAL SAFETY DATA SHEET**

---

**LIQUID POLYSTYRENE CEMENT**Revision Date: 18/04/2005

---

**Eye Contact:**

Remove victim immediately from source of exposure. Make sure to remove any contact lenses from the eyes before rinsing. Promptly wash eyes with plenty of water while lifting the eye lids. Continue to rinse for at least 15 minutes and get medical attention.

**Skin Contact:**

Remove affected person from source of contamination. Immediately remove contaminated clothing. Wash the skin immediately with soap and water. Get medical attention if irritation persists after washing.

**Ingestion:**

DO NOT induce vomiting. NEVER MAKE AN UNCONCIOUS PERSON VOMIT OR DRINK FLUIDS! Remove victim immediately from source of exposure. Immediately rinse mouth and provide fresh air. Get medical attention immediately! NOTE! Keep affected person away from heat, sparks and flames.

**5. FIRE FIGHTING MEASURES****Extinguishing Media:**

Fire can be extinguished using: Water spray, fog or mist. Alcohol resistant foam. Carbon dioxide (CO<sub>2</sub>). Dry chemicals, sand, dolomite, etc

**Special Fire-Fighting Procedures:**

Move container away from fire area if it can be done without risk. Containers close to fire should be removed or cooled with water. Cool containers exposed to flames with water until well after fire is out. Keep run-off water out of sewers and water courses. Dike for water control. Ventilate closed spaces before entering them.

**Usual Fire & Explosion Hazards:**

FLAMMABLE! Vapours are heavier than air and may spread near ground to sources of ignition. May travel considerable distance to source of ignition and flash back. Solvent vapours may form explosive mixtures with air.

**6. ACCIDENTAL RELEASE MEASURES****Spill Clean Up Methods:**

Wear necessary protective equipment. Extinguish all ignition sources. Avoid sparks, flames and smoking. Ventilate. Stop leak if possible without risk. Provide ventilation and confine spill. Do not allow run-off to sewer. Absorb in vermiculite, dry sand or earth and place in to containers. Containers with collected spillage must be properly labeled with correct contents and hazard symbol. Flush with plenty of water to clean spillage area. Do not let washing down water contaminate ponds or waterways.

**MATERIAL SAFETY DATA SHEET**

**LIQUID POLYSTYRENE CEMENT**

Revision Date: 18/04/2005

**7. HANDLING AND STORAGE**

**Usage Precautions:**

Static electricity and formation of sparks must be prevented. Keep away from heat, sparks and open flame. Use explosion proof electric equipment. Avoid spilling, skin and eye contact. Ventilate well, avoid breathing vapours. Use approved respirator if air contamination is above accepted level.

**Storage Precautions:**

Keep away from heat, sparks and open flame. Store in tightly closed original container in a cool, dry, well-ventilated place. Keep in original container. Ground container and transfer equipment to eliminate static electric sparks.

**Storage Class:**

Flammable liquid storage

**8. EXPOSURE CONTROLS/PERSONAL PROTECTION**

| Ingredient Name:     | STD: | LT - ppm: | LT – mg/m <sup>3</sup> : | ST - ppm: | ST – mg/m <sup>3</sup> : |
|----------------------|------|-----------|--------------------------|-----------|--------------------------|
| BUTYL ACETATE - norm | OES  | 150 ppm   | 724 mg/m <sup>3</sup>    | 200 ppm   | 966 mg/m <sup>3</sup>    |

**Ingredient Comments:**

OES = Occupational Exposure Standard

**Protective Equipment:**



**Engineering Measures:**

Explosion-proof general and local exhaust ventilation

**Respiratory Equipment:**

No specific recommendation made, but respiratory protection must be used if the general level exceeds the Recommended Occupational Exposure Limit.

**Hand Protection:**

Use protective gloves

**Eye Protection:**

Wear approved safety goggles. Contact lenses should not be worn when working with this chemical!

---

**MATERIAL SAFETY DATA SHEET**

---

**LIQUID POLYSTYRENE CEMENT**Revision Date: 18/04/2005

---

**Other Protection:**

Use engineering controls to reduce air contamination to permissible exposure level. Provide eyewash station and safety shower. Wear appropriate clothing to prevent any possibility of liquid contact and repeated or prolonged vapour contact. Wear appropriate clothing to prevent any possibility of skin contact.

**Hygienic Measures:**

DO NOT SMOKE IN WORK AREA!

Wash at end of each work shift and before eating, smoking and using the toilet. Promptly remove any clothing that becomes wet or contaminated.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**Appearance:** Liquid  
**Boiling Point:**  
**Relative Density:**  
**Vapour Pressure:**  
**Vapour Pressure:**  
**Viscosity:**  
**Flash Point (°C):**  
**Auto Ignition Temp:**  
**Flammability Limit – Lower (%):**  
**Flammability Limit – Upper (%):**

**10. STABILITY AND REACTIVITY****Stability:**

Stable under normal temperature conditions

**Conditions to Avoid:**

Avoid heat. Avoid contact with oxidisers or reducing agents.

**Hazardous Decomposition Products:**

Fire creates: Vapours/gasses/fumes of: Carbon monoxide (CO). Carbon Dioxide (CO<sub>2</sub>)

**11. TOXICOLOGICAL INFORMATION****Inhalation:**

Harmful by inhalation. Vapour from this chemical can be hazardous when inhaled. Vapour may affect central nervous system and cause headache, discomfort, vomiting or intoxication.

**Ingestion:**

May cause discomfort if swallowed. May cause stomach pain or vomiting.

**Skin Contact:**

Acts as a defatting agent on skin. May cause cracking of skin and eczema

---

**MATERIAL SAFETY DATA SHEET**

---

**LIQUID POLYSTYRENE CEMENT**Revision Date: 18/04/2005

---

**Eye Contact:**

Spray and vapour in the eyes may cause irritation and smarting

**Route of Entry:**

Inhalation, Ingestion, Skin and/or Eye contact

**12. ECOLOGICAL INFORMATION**

No information supplied

**13. DISPOSAL CONSIDERATIONS****DISPOSAL METHODS**

Dispose of waste and residues in accordance with local authority requirements. Do not allow run-off to sewer, waterway or ground

**14. TRANSPORT INFORMATION**

|                       |                            |                  |       |
|-----------------------|----------------------------|------------------|-------|
| PROPER SHIPPING NAME: | ADHESVIES                  | ADR CLASS No:    | 3     |
| UN NO. ROAD:          | 1133                       | ADR PACK GROUP:  | 5(b)  |
| ADR CLASS:            | Class 3: Flammable Liquids | ADR LABEL No:    | 3     |
| HAZARD No (ADR):      | 33                         | CEFIC TEC(R) No: | 30G80 |
| HAZCHEM CODE:         | 3(Y)E                      | RID PACK GROUP:  | 5(b)  |
| RID CLASS No:         | 3                          | IMDG CLASS:      | 3.2   |
| UN No. SEA:           | 1133                       | IMDG PACK GR:    | II    |
| IMDG PAGE No:         | 3174                       | MFAG:            | 330   |
| EMS:                  | 3-05                       | ICAO CLASS:      | 3     |
| UN No. AIR:           | 1133                       |                  |       |
| AIR PACK GR:          | II                         |                  |       |

---

**MATERIAL SAFETY DATA SHEET**

---

**LIQUID POLYSTYRENE CEMENT**Revision Date: 18/04/2005

---

**15. REGULATORY INFORMATION****Risk Phases:**

- R10** Flammable  
**R66** Repeated exposure may cause skin dryness or cracking  
**R67** Vapours may cause drowsiness and dizziness

**Safety Phases:**

- S2** Keep out of reach of children  
**S3** Keep in a cool place  
**S37** Wear suitable gloves  
**S46** If swallowed, seek medical advice immediately and show this container or label  
**S51** Use only in well-ventilated areas  
**S56** Dispose of this material and its container to hazardous or special waste collection point

**UK Regulatory References;**

Petroleum (Consolidation) Act: as amended 1984 SI 1244. Highly Liquid Regulations 1972

**Environmental Listing:**

Rivers (Prevention of Pollution) Act 1961. Control of Pollution (Special Waste Regulations) Act 1980

**EU Directives:**

System of specific information relating to Dangerous Preparations 2001/58/EEC. Dangerous Substance Directive 67/548/EEC. Dangerous Preparations Directive 1999/45/EEC

**Statutory Instruments:**

Chemicals (Hazard Information and Packaging) Regulations. Control of substances Hazardous to Health

**Approved Code of Practice:**

Classification and Labelling of Substances and Preparations Dangerous for Supply.  
Safety Data Sheets for Substances and Preparations

**Guidance Notes:**

Occupational Exposure Limits EH40  
Introduction to Local Exhaust Ventilation HS(G)37  
CHIP for everyone HSG(108).

**16. OTHER INFORMATION****Information Sources:**

Dangerous Properties of Industrial Materials Report, N Sax et al.

**Revision Date:** 18/04/20025

**REV. NO./REPL. SDS Generated:** 1

**SDS No:**

**Date:**

---

**MATERIAL SAFETY DATA SHEET**

---

**LIQUID POLYSTYRENE CEMENT**Revision Date: 18/04/2005

---

**Risk Phrases in Full:**

- R10** Flammable  
**R66** Repeated exposure may cause skin dryness or cracking  
**R67** Vapours may cause drowsiness and dizziness

**Disclaimer:**

All containers of HUMBROL products are labeled in accordance with the Chemical (Hazard Information and Packaging Regulations (CHIP)) to indicate any health and fire risks and the precautions to be taken. **BEFORE USING ANY PRODUCT READ THE LABEL NOTE PARTICULARLY ANY SPECIAL WARNINGS.**

HUMBROL products are supplied for use as specified, any changes in the usage of the products are the responsibility of the customer.

This information relates only to the specific material designated and not valid for such materials used in combination with any other materials or in any process. Such information is to the best of HUMBROL'S knowledge and belief accurate and reliable as of the date indicated.

However, no representation, warranty or guarantee is made as to its accuracy, reliability or completeness. It is the user's responsibility to satisfy himself as to the suitability and completeness of such information for his particular use.

---

‘1. Technology Supplies Limited (Company registration number 2285483) Whose registered office is Phoenix House, Tern Hill, Market Drayton, Shropshire, TF9 3PX (‘Technology Supplies’) is providing this data sheet on an ‘as is’ basis and makes no representations or warranties of any kind with respect to this data sheet or its contents and disclaims all such representations and warranties. In addition, Technology Supplies makes no representations or warranties about the accuracy, completeness, or suitability for any purpose of the information published in this data sheet. The information contained within this data sheet may contain technical inaccuracies or typographic errors. All liability of Technology Supplies howsoever arising for any such inaccuracies or errors is expressly excluded to the fullest extent permitted by law.

2. Neither Technology Supplies nor any of its directors, employees or other representatives will be liable for loss or damage arising out of connection with reliance upon this data sheet. This is a comprehensive limitation of liability that applies to damages of any kind, including (without limitation) compensatory, direct, indirect or consequential damages, income or profit, loss of or damage to property and claims of third parties.

3. Notwithstanding the foregoing, none of the exclusions and limitations in clauses 1 and 2 are intended to limit any rights you may have as a consumer under local law or other statutory rights which may not be excluded in any way to exclude or limit Technology Supplies for any liability for death or personal injury resulting in our negligence.’